

# PHILIPS

## CertaDrive

### LED driver



## Datasheet

### CertaDrive G2

CertaDrive 8W 0.2A 40V LPF I 230V

9290 014 80280

#### Affordable and reliable LED Drivers

Affordable LED Driver range offering Philips reliability. The CertaDrive range is compatible with COB and mid-power LEDs from any LED manufacturer.

#### Benefits

- Driver design based on Philips experience and knowledge of conventional fluorescent and HID technologies
- Various power wattage Drivers that are related to the lumen packages/applications
- Fixed output Drivers
- Independent-version housing design for stand-alone installations

#### Features

- High reliability
- Luminaire design flexibility to keep stable/constant
- Lumen output and light quality levels
- Fast Time to Market
- One supplier for professional general lighting LED Drivers
- Affordable LED Drivers

#### Application

- Public buildings (airports, cinemas, theaters, exhibition halls)
- Retail (supermarkets, shops)
- Office

## Electrical input data

| Specification item          | Value     | Unit            | Condition                                  |
|-----------------------------|-----------|-----------------|--------------------------------------------|
| Rated input voltage range   | 220...240 | V <sub>ac</sub> | Performance range                          |
| Rated input voltage         | 230       | V <sub>ac</sub> |                                            |
| Rated input frequency range | 50...60   | Hz              | Performance range                          |
| Rated input current         | 0.11      | A               | @ rated output power @ rated input voltage |
| Rated input power           | 10.5      | W               | @ rated output power @ rated input voltage |
| Power factor                | 0.5       |                 | @ rated output power @ rated input voltage |
| Efficiency                  | ≥ 77      | %               | @ rated output power @ rated input voltage |
| Input voltage AC range      | 202...254 | V <sub>ac</sub> | Operational range                          |
| Input frequency AC range    | 47.5...63 | Hz              | Operational range                          |
| Isolation input to output   | SELV      |                 |                                            |

## Electrical output data

| Specification item       | Value            | Unit            | Condition                   |
|--------------------------|------------------|-----------------|-----------------------------|
| Regulation method        | Constant Current |                 |                             |
| Output voltage           | 30...40          | V <sub>dc</sub> |                             |
| Output voltage max.      | 60               | V               | Peak voltage at open load   |
| Output current           | 0.2              | A               | Full output current setting |
| Output current tolerance | ± 10             | %               |                             |
| Output current ripple LF | ≤ 5              | %               | Ripple = peak / average     |
| Output power             | 6...8            | W               | Full output                 |

## Electrical data controls input


| Specification item | Value | Unit | Condition |
|--------------------|-------|------|-----------|
| Control method     | Fixed |      |           |

## Logistical data

| Specification item | Value                             |
|--------------------|-----------------------------------|
| Product name       | CertaDrive 8W 0.2A 40V LPF I 230V |
| Logistic code 12NC | 9290 014 80280                    |
| Pieces per box     | 60                                |


## Wiring & Connections

| Specification item        | Value     | Unit            | Condition                                            |
|---------------------------|-----------|-----------------|------------------------------------------------------|
| Input wire cross-section  | 0.2...1.5 | mm <sup>2</sup> | DA250 (3.5 mm), solid / stranded wire                |
|                           | 16...24   | AWG             | DA250 (3.5 mm), solid / stranded wire                |
| Input wire strip length   | 8.5...9.5 | mm              |                                                      |
| Output wire cross-section | 0.2...1.5 | mm <sup>2</sup> | DA250 (3.5 mm), solid / stranded wire                |
|                           | 16...24   | AWG             | DA250 (3.5 mm), solid / stranded wire                |
| Output wire strip length  | 8.5...9.5 | mm              |                                                      |
| Maximum cable length      | 600       | mm              | Total length of wiring including LED module, one way |



## Dimensions and weight

| Specification item        | Value | Unit | Condition |
|---------------------------|-------|------|-----------|
| Length (A1)               | 88    | mm   |           |
| Width (B1)                | 39    | mm   |           |
| Height (C1)               | 22    | mm   |           |
| Fixing hole diameter (D1) | 3.3   | mm   |           |
| Fixing hole distance (A2) | 79    | mm   |           |
| Weight                    | 100   | gram |           |




## Operational temperatures and humidity

| Specification item          | Value     | Unit | Condition                                                               |
|-----------------------------|-----------|------|-------------------------------------------------------------------------|
| Ambient temperature         | -20...+45 | °C   | Higher ambient temperature allowed as long as Tcase-max is not exceeded |
| Tcase-max                   | 75        | °C   | Maximum temperature measured at T <sub>case</sub> -point                |
| Tcase-life                  | 65        | °C   | Measured at T <sub>case</sub> -point                                    |
| Maximum housing temperature | 130       | °C   | In case of a failure                                                    |
| Relative humidity           | 10...90   | %    | Non-condensing                                                          |

## Lifetime

| Specification item | Value  | Unit  | Condition                                                                 |
|--------------------|--------|-------|---------------------------------------------------------------------------|
| Driver lifetime    | 30,000 | hours | Measured temperature at Tcase-point is Tcase-life. Maximum failures = 10% |



## Storage temperature and humidity

| Specification item  | Value     | Unit | Condition      |
|---------------------|-----------|------|----------------|
| Ambient temperature | -25...+85 | °C   |                |
| Relative humidity   | 5...95    | %    | Non-condensing |

## Programmable features

| Specification item                    | Value | Remark               | Condition                        |
|---------------------------------------|-------|----------------------|----------------------------------|
| Set output current (AOC)              |       | See Design-in guide. | Default output current: = 200 mA |
| LED module temperature derating (MTP) | No    |                      |                                  |
| Driver Temperature Limit (DTL)        | No    |                      |                                  |
| Constant Lumen Over Lifetime (CLO)    | No    |                      |                                  |
| DC emergency dimming (DCemDIM)        | No    |                      |                                  |
| Corridor mode                         | No    |                      |                                  |
| Energy metering                       | No    |                      |                                  |
| Diagnostics                           | No    |                      |                                  |

## Features


| Specification item                          | Value | Remark | Condition            |
|---------------------------------------------|-------|--------|----------------------|
| Open load protection                        | Yes   |        | Automatic recovering |
| Short circuit protection                    | Yes   |        | Automatic recovering |
| Over power protection                       | Yes   |        | Automatic recovering |
| Hot wiring                                  | No    |        |                      |
| Suitable for fixtures with protection class | II    |        | per IEC60598         |

## Certificates and standards

| Specification item                     | Value                |
|----------------------------------------|----------------------|
| Approval marks                         | CB / CCC / CE / ENEC |
| Ingress Protection classification (IP) | 20                   |

## Inrush current

| Specification item         | Value     | Unit    | Condition                                      |
|----------------------------|-----------|---------|------------------------------------------------|
| Inrush current $I_{peak}$  | 9         | A       | Input voltage 230V                             |
| Inrush current $T_{width}$ | 250       | $\mu s$ | Input voltage 230V, measured at 50% $I_{peak}$ |
| Drivers / MCB 16A type B   | $\leq 60$ | pcs     | Indicative value                               |



| MCB | Rating | Relative number of LED drivers |
|-----|--------|--------------------------------|
| B   | 4A     | 25%                            |
| B   | 6A     | 40%                            |
| B   | 10A    | 63%                            |
| B   | 13A    | 81%                            |
| B   | 16A    | 100% (stated in datasheet)     |
| B   | 20A    | 125%                           |
| B   | 25A    | 156%                           |
| B   | 32A    | 200%                           |
| B   | 40A    | 250%                           |
| C   | 4A     | 42%                            |
| C   | 6A     | 63%                            |
| C   | 10A    | 104%                           |
| C   | 13A    | 135%                           |
| C   | 16A    | 170%                           |
| C   | 20A    | 208%                           |
| C   | 25A    | 260%                           |
| C   | 32A    | 340%                           |
| C   | 40A    | 415%                           |

## Driver touch current / protective conductor current


| Specification item                    | Value | Unit    | Condition                                             |
|---------------------------------------|-------|---------|-------------------------------------------------------|
| Typical touch current (ins. Class II) | 0.7   | mA peak | Acc. IEC61347-1. LED module contribution not included |

## Surge immunity


| Specification item                | Value | Unit | Condition                                   |
|-----------------------------------|-------|------|---------------------------------------------|
| Mains surge immunity (diff. mode) | 0.5   | kV   | Acc. IEC61000-4-5. 2 Ohm, 1.2/50us, 8/20us  |
| Mains surge immunity (comm. mode) | 1     | kV   | Acc. IEC61000-4-5. 12 Ohm, 1.2/50us, 8/20us |

Graphs


Operating window



Power factor versus output power



Efficiency versus output power





©2019 Signify Holding, IBRS 10461, 5600 VB, NL. All rights reserved.

The information provided herein is subject to change without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

Date of release: May 31, 2019 v11

[www.philips.com/oem](http://www.philips.com/oem)