

**KRN-M16/-95****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

**The use of insulated connectors guarantees users consistent electrical connection quality in the long term.**

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

**General ordering data**

|            |                                             |
|------------|---------------------------------------------|
| Version    | cable lug, terminal end, 95 mm <sup>2</sup> |
| Order No.  | <a href="#">1495630000</a>                  |
| Type       | KRN-M16/-95                                 |
| GTIN (EAN) | 4050118305326                               |
| Qty.       | 25 pc(s).                                   |

## KRN-M16/-95

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |        |
|------------|--------|
| Net weight | 57.8 g |
|------------|--------|

## Technical data

|         |                       |
|---------|-----------------------|
| Version | Euro series, standard |
|---------|-----------------------|

## Connectors

|                                |                    |                                |         |
|--------------------------------|--------------------|--------------------------------|---------|
| Conductor cross-section        | 95 mm <sup>2</sup> | Connection length (l)          | 51 mm   |
| Flange width (b)               | 28 mm              | Hole                           | M16     |
| Inside diameter of flange (d2) | 17 mm              | Inside diameter of shaft (d1)  | 13.5 mm |
| Insulation                     | not available      | Outside diameter of shaft (d3) | 18 mm   |
| Shaft length (a)               | 23 mm              |                                |         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001051    | ETIM 7.0    | EC001051    |
| ETIM 8.0    | EC001051    | ECLASS 9.0  | 27-40-02-05 |
| ECLASS 9.1  | 27-40-02-05 | ECLASS 10.0 | 27-40-02-05 |
| ECLASS 11.0 | 27-40-02-05 | ECLASS 12.0 | 27-40-02-05 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

## KRN-M16/-95

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

