

TRANSCLINIC BKE 1K0.4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**String monitoring with Transclenic xi+**
A system that permanently monitors the performance of photovoltaic facilities.

The Transclenic xi+ series continuously monitors the power from single strings or groups of strings as well as the voltage of a Photovoltaic system and thereby permits detailed monitoring of the system. Negative influences, which lead to reduced output, can be detected immediately allowing rapid repairs or adjustments to be made to the system.

General ordering data

Version	Photovoltaics, Power supply unit, Monitoring components, 1000 V
Order No.	7791400746
Type	TRANSCLINIC BKE 1K0.4
GTIN (EAN)	8430243294287
Qty.	1 pc(s).

TRANSCLINIC BKE 1K0.4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	71 mm	Depth (inches)	2.795 inch
Height	90 mm	Height (inches)	3.543 inch
Width	71 mm	Width (inches)	2.795 inch
Net weight	230 g		

Temperatures

Ambient temperature	-35 to +70°C	Continuous operating temp., min.	-35 °C
Continuous operating temp., max.	70 °C		

Technical data

Pollution severity		Standards	IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV, IEC 61000-4-4:2012, IEC 61000-4-2
	2		
Voltage supply	300 V DC - 1000 V DC		

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
ETIM 8.0	EC002928	ECLASS 9.0	22-57-92-03
ECLASS 9.1	22-57-04-90	ECLASS 10.0	22-57-04-90
ECLASS 11.0	22-57-02-92	ECLASS 12.0	22-57-02-92

Downloads

Catalogues	Catalogues in PDF-format
------------	--