

QUARTZ CRYSTAL UNIT

*Seam Sealed Ceramic 3.2*2.5mm Surface Mount Package*



Approved by:
Checked by:
Issued by:

SPECIFICATION

P/N: KSE-7U40000MAZ143ZA3

CompoNet Ltd

sh. Khoroshyovskoe, 43V, Moscow, Russia, 123308

Tel: +7 (495) 204-13-84 Email: sale@radiodetali.com

The design, manufacturing process, and specifications of this device are subject to change without notice.

Page 1 of 5

QUARTZ CRYSTAL UNIT

Seam Sealed Ceramic 3.2*2.5mm Surface Mount Package



FEATURE

- I Reliable seam sealed ceramic package.
- I Wide operating temperature range.
- I Superior performance and stringent reliability in harsh environment.
- I Application: TPMS, ECM, ABS and sensor modules.
- I Compact size.
- I RoHS Compliant / Pb Free.

ELECTRICAL SPECIFICATIONS

Output Frequency Range	40.000 MHz
Mode	AT/Fundamental
Frequency Tolerance (at 25°C)	±10ppm
Frequency Stability Over Operating Temperature Characteristics	±30ppm
Operating Temperature Range	-40 °C to +85 °C
Storage Temperature Range	-40 °C to +85 °C
Shunt Capacitance (C0)	5.0 pF Max
Driver Level (Typical)	100μW
Load Capacitance(CL)	7pF
Equivalent Series Resistance(ESR)	40Ω Max


The design, manufacturing process, and specifications of this device are subject to change without notice.

QUARTZ CRYSTAL UNIT


Seam Sealed Ceramic 3.2*2.5mm Surface Mount Package



DIMENSION



REFLOW CONDITION



①	Preheat	150±5°C	120sec.
②	Peak	260°C	10sec. max.

Total time 200sec. max. Solder melting point: 185°C


The reflow temperature profile may vary depending on the product model, specifications and frequency range. Refer to the individual product specifications for details.

QUARTZ CRYSTAL UNIT

Seam Sealed Ceramic 3.2*2.5mm Surface Mount Package



PACKING



DIMENSIONS		A	B	C	D	E	L	L1	W	W1	pcs / Reel
	7050	2.15	7.9	5.4	8	16	180	13	21.5	17.5	1K
	6035	1.4	6.4	3.9	8	12	180	13	15.4	13	1K
	5032	1.46	5.5	3.6	8	12	180	13	15.4	13	1K
	3225	1.4	3.4	2.7	4	8	180	13	11.5	8	3K
	2520	1.15	2.8	2.25	4	8	180	13	10.5	8	3K
	2016	0.95	2.25	1.85	4	8	180	13	10.5	9	3K
	1612	0.8	1.85	1.45	4	8	180	13	10.5	9	3K

The design, manufacturing process, and specifications of this device are subject to change without notice.

QUARTZ CRYSTAL UNIT

Seam Sealed Ceramic 3.2*2.5mm Surface Mount Package



RELIABILITY TEST SPECIFICATION

Test item	Equipment	Condition	Specification
1.SOLDERABILITY TEST	TBAEI ESPEC(K-1425-14D)	Welding can be temperature: $260 \pm 5^{\circ}\text{C}$, 5's(125 $^{\circ}\text{C}$, 120 SEC preheating Anti-welding temperature: $260 \pm 5^{\circ}\text{C}$, soaking time: 10 seconds	MIL-STD-883E Method 2003.7
2. HERMETICITY TEST	Helium leak detectors	1. Small leak: 4.5 KGF/CM2 2hours1 * 10-9-9 PA.M3/SEC crude leak: 4.5KGF/CM2 2hours1.5 * 10-5 PA.M3/SEC	MIL-STD-883E Method 1014.10
3. VIBRATION TEST	Sweep vibration test machines (IMV CO. (VS-300-2)), S & A250B	1 Crystal on 10-2000 Hz, X, Y, Z water level, each 20-minute vibration, a test every four hours, then the sample used to test 250 b	MIL-STD-883E Method 2007.3
4. MECHANICAL SHOCK	TOOL	A high degree of crystal from 150 CM to 150 g of three months from the direction of impact XYZ3 work hard wooden board	JIS C6701
5.MECHANICAL IMPACT TEST	TOOL	c1000G, 0.5Msec, 3, from the X, Y, Z three-day direction of hard wood boards, then the sample used to test 250 B	MIL-STD-202F Method 213B
6. DROP TEST	Fell hard wood equipment, S & A 250B	Crystal 75 cm in height, falling three times in the hard wooden board	JIS C6701
7. SALT SPRAY	H-SST-60、RC-328A	5% NaCL (sodium carbonate), 35 $^{\circ}\text{C} \pm 2^{\circ}\text{C}$ temperature of the box, 48 hours, PH value: 6.5 to 7.2	
8. HIGH&LOW TEMP STORAGE TEST	TABEL ESPEC(MC-810), S&A 350B/250B	High temperature: $125^{\circ}\text{C} \pm 2^{\circ}\text{C}$, 500 hours; low temperature: $-40^{\circ}\text{C} \pm 3^{\circ}\text{C}$, 500hours	MIL-STD-883E Method 1005.8
9. TEMP& HUM CYCLING TEST	TABEI ESPEC (TPC-211) S&A350B/250B	Temperature: $121 \pm 3^{\circ}\text{C}$ RH100% 2BAI, 240hours	JIS C6701
10. HIGH TEM. & HUM. STORAGE TEST	TBAEL ESPEC (PH-3F) , S&A350B/250B	Temperature: $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$, Humidity: 85 +3, -2%, storage 96 hours	JIS C5023
11.AGING TEST	PRA(2360)	Temperature: $85^{\circ}\text{C} \pm 2^{\circ}\text{C}$, 1000hours	JIS C6701

The design, manufacturing process, and specifications of this device are subject to change without notice.