




Model	Output Current	Input Current	Input Power	Output Power Range	PF	Efficiency	Output Voltage	No load Voltage
LC50W150-300	150mA	0.14A	29.0W	7.5-25.5W	0.90	90%	50-170V	250V
	200mA	0.18A	38.0W	10.0-34.0W	0.90	90%		
	250mA	0.22A	47.0W	12.5-42.5W	0.92	91%		
	300mA	0.26A	56.0W	15-51.0W	0.95	92%		

* Test result @230V, 50Hz, Full Load.

1.Parameters

category	Item	Technical Norm
Features	Output Type	Constant Current
	IP Grade	IP20
	Insulation Class	Class I
Input	Rated Input Voltage	220-240V
	Range of AC Input Voltage	198-264VAC
	Range of DC Input Voltage	176-280VDC
	Frequency	0/50-60Hz
	Power Factor	≥0.95(230VAC, full Load, see graphs)
	THD	≤20%(230VAC, full Load, see graphs)
	No-load Power Consumption	≤0.5W @230VAC
	Current Accuracy	±5%
	Max. Output Voltage	250V
	Started Delay Time	≤0.5S (230VAC, full load)
	Current Ripple(< 120 Hz)	±5% (Imax-Imin) / (Imax+Imin)

Output	PstLM	≤1
	SVM	≤0.4
	Emergency output coefficient	1
Protection	Short Circuit Protection	Auto Recovery
	Overload Protection	Auto Recovery
	No-load Protection	Auto Recovery
	Insulation voltage	O/P to PE , 1.5KVac/1min I/P to PE , 1.5KVac/1min
	Insulation resistance	>100M ohm @ 500VDC
	Leakage current	I/P to O/P < 700μA
Environment	Ta/Operation Temperature	-20...+55℃
	Ts/Storage Temperature	-30....+85℃
	Tc/Enclosure Temperature	75℃
	Humidity	10%....90%RH
	Atmosphere	86-108KPa
Construction	Connection Method	Push-in Terminal
	Installation	Build-in
	PRI Wire preparation	0.5-1.5□
	SEC Wire preparation	0.5-1.5□
	Dimension	230*30*21mm (L*W*H)
Standards	Certification	CE、ENEC、EAC、UKCA、SAA
	Safety Standards	EN61347-1:2015 EN61347-2-13:2014/A1:2017 EN62384:2006/A1:2009 EN62493:2015 AS61347.2.13:2018 AS/NZS61347.1:2016 Inc A1
	EMC Standards	EN IEC 55015:2019 EN61547:2009 EN IEC 61000-3-2:2019 EN 61000-3-3:2013/A1:2019
	Performance	EN62384
	Surge	L-N:1KV; L/N-PE:2KV;
	RoHS	Complied to 2011/65/EU
Others	Life Time	50000h Tc=75℃, F.R. <10%
		75000h Tc=70℃, F.R. <10%
		100000h Tc=65℃, F.R. <10%
	Warranty	5years
Remark: 1.All Parameters, if not specified, are measured at 230VAC/50Hz and 25℃ ambient temperature. 2.LED Driver is a component of the luminaires. Luminaires and wire layout will affect the EMC, please check the EMC with end products again.		



LC50W150-300

2.Output Current Setting

Output Current	Dial 1	Dial 2
300mA	ON	ON
250mA	OFF	ON
200mA	ON	OFF
150mA	OFF	OFF

3.Connected quantities of different current Breaker

TYPE	LC50W150-300 Connected quantities of different current Breaker						Input Voltage	Inrush Current	Time
	current (A)	10	13	16	20	25			
	Installation wire diameter	1.5mm ²	2.5mm ²	2.5mm ²	4mm ²	4mm ²			
TYPE B		24	31	38	48	60	@230VAC	25	250us
TYPE C		38	50	61	77	96			
TYPE D		61	80	98	123	154			

4.Label


☐
☐ N
☐ L

KGP
KGP Electronics GmbH
Hueckstraße 19
DE-58511 Lüdenscheid
LED Driver
LC50W150-300
Constant Current Type


PIN1	PIN2	I _{rated} (mA)	P _{rated} (W)	U _{rated} (V)	U _N / f _N	I _N (A)	ta (°C)	λ	
OFF	OFF	150	25.5	50-170	220-240V 0/50-60Hz	0.14	-20...+55	0.90C	
ON	OFF	200	34			0.18		0.90C	
OFF	ON	250	42.5			0.22		0.92C	
ON	ON	300	51			0.26		0.95	

U_{out} : Max.250VDC For LED modules only Made in China

5.Lifetime curve




6.Dimension (Unit: mm)



7.Packing information

Carton L*W*H(mm)	Pcs/Carton	Net weight/ Pcs(kg)	Net weight/ Carton(kg)	Gross weight / Carton(kg)
410*270*160MM	60PCS	T.B.D	T.B.D	T.B.D

8.Wiring Diagram



9.Wiring instructions

- All connections must be kept as short as possible to ensure good EMI behaviour
- Mains leads should be kept apart from LED Driver and other leads (ideally 5 – 10 cm distance)
- Advice the maximum length of output wires is 3 m
- Secondary switching is not permitted (Except for constant voltage)
- Incorrect wiring can damage LED modules.
- The wiring must be protected against short circuits to earth (sharp edged metals parts, metal cable clips, louver, etc.)
- The lamp controlgear relies upon the luminaire enclosure for protection against accidental contact with live parts.

10.REVISION HISTORY

DATE	REV.	REMARK
2022-10-26	V1.0	Initial release.
2022-12-14	V1.1	Update the label.