



TINY圆形端子式

纹波电流: $\pm 5\%$	Current Ripple: $\pm 5\%$
保护种类: 开路/短路/过载	Protection: Open Circuit/Short Circuit/Overload
防护等级: IP20	Ingress Protection: IP20
启动时间: $<0.5S/220V$	Start Time: $<0.5S/220V$
工作温度: $-20\sim 60^{\circ}C$	Ambient Temp: $-20\sim 60^{\circ}C$
存储温度: $-30\sim 85^{\circ}C$	Storage Temp: $-30\sim 85^{\circ}C$
5年质保	5 Years Warranty
认证: TUV/CE/CCC/SAA	Certificates: TUV/CE/CCC/SAA
应用: 筒灯	Application: Downlight
外壳尺寸: 8-14W:42×20.2mm	Size: 8-14W: 42×20.2mm
27-30W:49×22.5mm	27-30W:49×22.5mm
27-30W:55×25mm	27-30W:55×25mm
36-42W:64×25mm	36-42W:64×25mm

型号	额定功率	输入电压	输出电压	输出电流	效率(满载)	功率因数(满载)	认证
Model	Rated Load	Input Voltage	Output Voltage	Output Current	Efficiency (full load)	Power factor (full load)	Safety Certificates
RC8W200A7	5.40-8.00W	220-240VAC 50/60Hz	27-40V	200mA	80%	0.5	TUV/CE/CCC/SAA
RC10W250A7	6.75-10.00W	220-240VAC 50/60Hz	27-40V	250mA	82%	0.5	TUV/CE/CCC/SAA
RC12W300A7	8.10-12.00W	220-240VAC 50/60Hz	27-40V	300mA	82%	0.5	TUV/CE/CCC/SAA
RC14W350A7	9.45-14.00W	220-240VAC 50/60Hz	27-40V	350mA	82%	0.5	TUV/CE/CCC/SAA
RC8W200	3.00-8.40W	220-240VAC 50/60Hz	24-42V	200mA	80%	0.9	TUV/CE/CCC/SAA
RC10W250	3.75-10.50W	220-240VAC 50/60Hz	24-42V	250mA	80%	0.9	TUV/CE/CCC/SAA
RC12W300	4.50-12.60W	220-240VAC 50/60Hz	24-42V	300mA	80%	0.9	TUV/CE/CCC/SAA
RC16W350-400	5.25-14.70W	220-240VAC 50/60Hz	15-42V	350mA	87%	0.9	TUV/CE/CCC/SAA
	6.00-16.80W	220-240VAC 50/60Hz	15-42V	400mA	88%	0.9	TUV/CE/CCC/SAA
RC21W450-500	6.75-18.90W	220-240VAC 50/60Hz	15-42V	450mA	87%	0.9	TUV/CE/CCC/SAA
	7.50-21.00W	220-240VAC 50/60Hz	15-42V	500mA	88%	0.9	TUV/CE/CCC/SAA
RC27W600-650	9.00-25.2W	220-240VAC 50/60Hz	15-42V	600mA	86%	0.9	TUV/CE/CCC/SAA
	9.80-27.3W	220-240VAC 50/60Hz	15-42V	650mA	86%	0.9	TUV/CE/CCC/SAA
RC31W700-750	10.50-29.40W	220-240VAC 50/60Hz	15-42V	700mA	87%	0.92	TUV/CE/CCC/SAA
	11.30-30.00W	220-240VAC 50/60Hz	15-42V	750mA	88%	0.95	TUV/CE/CCC/SAA
RC36W800-850	12.00-33.60W	220-240VAC 50/60Hz	15-42V	800mA	88%	0.92	TUV/CE/CCC/SAA
	12.80-35.70W	220-240VAC 50/60Hz	15-42V	850mA	88%	0.92	TUV/CE/CCC/SAA
RC42W900-1000	13.50-37.80W	220-240VAC 50/60Hz	15-42V	900mA	89%	0.92	TUV/CE/CCC/SAA
	15.00-42.00W	220-240VAC 50/60Hz	15-42V	1000mA	89%	0.95	TUV/CE/CCC/SAA