


SPECIFICATION FOR APPROVAL

CUSTOMER : COMPONET	DATE : 29-03-2016 DD/MM/YYYY	
CUSTOMER P/N : PLA10AN(S)5521R0R2		
C.T.C. P/N : UU11-610022-B	SAMPLEQ'TY :	
PRODUCT NAME : UU11-552N-040-VER00		
DRAWN BY:	CHECKED BY:	APPROVED BY:
Chen Boyuan	Chen Boyuan	Tao Guowen

APPROVED BY CUSTOMER

	SIGNATURE	DATE
APPROVED		
CONDITIONAL APPROVED		
REJECTED		



C.T.C. Coils Limited

確力新實業有限公司

香港新界大埔汀角路 55 號太平工業中心 2 座 8 字樓 E 室
Flat E, 8/F., Block 2, Tai Ping Ind. Centre, 55 Ting Kok Rd.,
Tai Po, N.T., Hong Kong.

Tel : (852) 26954889 Fax : (852) 26951842
http : //www.ctccoils.com E-mail : enquiry@ctccoils.com

C.T.C. Electronics (Fonggang) Limited

東莞鳳崗確力新電子有限公司

中國廣東省東莞市鳳崗鎮雁田區南山工業城 B-01 棟
No. B-01, Nanshan Ind. District, Yantian Village, Fenggang Town,
Dongguan City, Guangdong Province, China.

Tel : (86) 769-87771591 Fax : (86) 769-87771314

SPECIFICATION FOR: COMPONET

(OS1) REF.: PLA10AN(S)5521R0R2




C.T.C. P/N: UU11-610022-B

DATE: DD/MM/YYYY 29-03-2016



PRODUCT NAME: UU11-552N-040-VER00

1.DIMENSION (UNIT : mm):



A: 19.0 Max.	B: 22.0 Max.	C: 4.0 ± 1.0	D: 17.0 Max.	E: 0.70 ± 0.10
F: 13.0 ± 0.5	G: 10.0 ± 0.5	H:	I:	J:

2.ELECTRIC CHARACTERISTICS: (TEST AT : 24°C ± 4°C)

INDUCTANCE: 5.5 mH Min.	TEST FREQ: @1.0KHz/0.25V	DCR: 193.7 mΩ Max.
TURNS: 35TS Ref.	IR: 100 MΩ Min.	RDC: 1.0 A
Q: --- Min @ --- MHz	SRF: --- MHz Min.	TEMP: -20°C ~ +80°C

3.TEST EQUIPMENT:

☐ HP-4284A (LCZ-METER)	☐ CH-1062 (LCZ-METER)	☒ CH-1320(CURRENT METER)
☐ HP-8712C (ANALYZER)	☐ SK-3005 (INSULATION TESTER)	☐ MQ-1601 (Q-METER)
☒ CH-100 (LCR-METER)	☐ CH-852A (HIGH POT TEST METER)	☐ HL-2801 (ANALYZER)
☒ HK502BC (DCR-METER)	☐	☐

4. MATERIALS:

CORE: UU10.5 AL>3500				PIN: ---	
WIRE: ϕ 0.40mm		2UEW-F		155°C ---kg/kpcs	
TAPE: --- mm		(MARK'G: --- COLOR: ---) ---m/kpcs			
VARNISH: 凡立水			BOBBIN & BASE: UU10.5		
GLUE: ----		N.W: 7.30 kg/kpcs		PACKING: PLASTIC SACK	

5.NOTE:

DRAWN: Chen Boyuan CHECKED: Chen Boyuan APPROVED: Tao Guowen