Primary Lithium Battery
CR-P2

6.0V [Li-MnO_2]



BENEFITS

- High Voltage Response, Stable During Most of the Lifetime of the Application
- Energy Density up to 830Wh/L
- Wide Operating Temperature Range (-40℃~+85℃)
- Low Self-discharge Rate (less than 1% per year after 1 year of storage at +25℃)

KEY FEATURES

- Optimized Battery Structure, Full Discharge Capacity
- Long Endurance
- No passivation
- GB 8897.4-2008, IEC 60086.4:2014 and RoHS

MAIN APPLICATIONS

- Security System
- Smart Metering
- RFID and Tracking System
- Wireless Transmitting
- Smart Home Devices
- Military Devices

References Data

Electrical characteristics


Open circuit voltage (at 25°C)	≥6.2V
Nominal capacity	1500mAh
(At +25°C, battery discharged at continuous current 5mA until voltage reaches cut-off voltage 4.0V. The capacity can vary at different temperature, discharge current or cut-off voltage.)	
Maximum continuous current	1500mA
(At +25°C, 4.0V cut-off, battery discharged for minimum 50% of rated capacity.)	
Maximum pulse discharge current	3000mA
(At +25°C, 4.0V cut-off, battery discharged for minimum 50% of rated capacity with max pulse for 3 seconds after 27 seconds break. For more battery capacity, please consult HCB.)	
Storage (recommended)	≤+30°C
(For more severe conditions, consult HCB.)	≤75%RH
Operating temperature range	-40°C~+85°C
(Operation above ambient temperature may lead to reduced capacity and lower voltage readings at the beginning of pulses. Consult HCB.)	

HCB BATTERY CO., LTD
Add：37 Tianyuan Street, Dongxihu District, Wuhan, Hubei, China
P.O.：430040
Tel：+86(0)27 83248452
Fax：+86(0)27 83248455
Email：haocheng@cnhcb.com
Web：www.cnhcb.com
No.: HCB-MKT.PM-S[V2.0 2023 05]

Primary Lithium Battery
CR-P2


6.0V [Li-MnO_2]

Physical characteristics	
Width	34.0±1.0mm
Height	35.5±0.5mm
Thickness	19.0±0.5mm
Typical weight	45.0g
Li metal content	1.08g




Dimensions in mm（GB1804-m）


1.Typical discharge profiles at 25°C
(at mid-discharge)



2.Voltage plateau versus Current and Temperature
(at discharge stable phase)



3.Storage characteristics



WARNING:

- Do Not Short Circuit
- Do Not Recharge
- Do Not Puncture
- Do Not Crush
- Do Not Dismantle
- Do Not Incinerate
- Do Not Mix New and Used Batteries
- Do Not Heat Above 100°C

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries . Cell and battery designs/specif -ications are subject to modification withour notice.
Contact HCB for the latest information

HCB BATTERY CO., LTD
Add：37 Tianyuan Street, Dongxihu District, Wuhan, Hubei, China
P.O.：430040
Tel：+86(0)27 83248452
Fax：+86(0)27 83248455
Email：haocheng@cnhcb.com
Web：www.cnhcb.com

No.: HCB-MKT.PM-S[V2.0 2023 05]